

## Domed polycarbonate diffuser luminaires


Highly efficient back-lit luminaires with a domed, polycarbonate diffuser.

SkyDome is part of the SkyCore family, a range of luminaires designed with sustainability and circularity principles in mind. SkyCore luminaires use the Fast-Fix wiring enclosure and Thorlux patented LUX Guard technology for fast installation, future flexibility and prolonged life.

Available in; recessed, surface and pendant mounting options.

Applications: classrooms, libraries, healthcare, break-out areas, canteens, circulation areas and entrance lobbies.

- Shallow body depth of 59 mm, 94 mm including the gearbox
- TM66 score of 2.7 - LIA/CIBSE certification scheme TSD-012 verified
- Domed diffuser provide excellent wall, ceiling and vertical illumination
- Suitable for most ceiling types with optional side arm suspensions and plasterboard mounting kits
- Designed to exclude dust, dirt and flies. All control gear is outside the LED enclosure
- Rapid installation using Fast-Fix wiring enclosure or SmartScan plug and play TEE connectors
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit



Up to IP40 (IP20 above ceiling)

Up to IK09

Up to 150.6 LL/CW

SMARTSCAN

LUXGUARD

TM66 circularity score 2.7

## Specification

Mounting	Recessed Surface Suspended	IP rating	Up to IP40 (IP20 above ceiling)
Impact rating	Up to IK09	Nominal size	600 x 600 mm
Max presence detection height	8 m		

## Sustainability

TM66 circularity score	2.7
------------------------	-----

## Lighting

Optic	Opal diffuser	Lumen output	2,710 lm - 5,315 lm
Efficacy	Up to 150.6 LL/CW		

## Emergency data

Emergency lumen output	330 lm	Emergency type	Maintained
Emergency duration	3 hours	Battery specification	Nickel Metal Hydride (NiMH)

## Power

LED power	15 W - 33 W	Circuit power	18 W - 37 W
-----------	-------------	---------------	-------------


## LED characteristics

CRI	80+	Colour temperature	4000 K
Rated life (hours)	100 K - L90/B10		

## Compliance

SmartScan wireless standards compliance	<p>Europe: EN 300 220-1 V2.4.1/ EN 301 489-3 V1.6.1. Australasia: ACMA 2014 Radio Communication Standard 2014. Thorlux Patented Wireless Technology - GB2575724</p>
---	---

## Dimensions



View the range



Information is correct as of 21 Nov 2024, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.